



## La Marzocco Strada EE 3 Group

In an aim to complete the Strada line of models, the Strada EE is characterized by its underlying mechanical and electronic features (semi-automatic technology) built within the design of the Strada. The initials "EE" refer to a feature whereby brewing is activated by the simple start & stop motion of the paddle on the group head, albeit with electronic pre-infusion. The Strada EE model includes individual brew boilers, proportional steam valves featuring anti-suction valves, a thermal stability system and easy-access for preventative maintenance. The semi-automatic paddle is inspired by the paddle used on most La Marzocco machines since the 1970s. It is controlled with La Marzocco's classic paddle interface, manually operated by the barista.

- Dual boilers, Separate boilers optimize espresso brewing and steam production
- PID allows you to electronically control espresso brewing temperature
- Saturated Group ensure unsurpassed thermal stability, shot after shot
- Stainless steel portafilters and precision baskets improve your cup quality and consistency
- Cup warmer maintains espresso and cappuccino cups heated at a proper temperature
- Tall cups facility allows you to use the machine with tall, to-go cups
- Led lighting allows you to focus on your extraction and the cup
- Cronos keypad with digital shot timer to monitor the extraction time (AV version only)

Weight 102 kg  
Dimensions 475 H mm. x 1000 W mm. x 675 D mm.  
Boiler Capacity 11.8 Litres  
Amps 45  
Watts 6.4kw



01744 762919



sales@coffee1652.couk



Coffee 1652 Unit 1, Ketterer Court, Jackson Street St Helens WA9 3AH

